

# INDUSTRIAL DEHUMIDIFIERS

HUMIDITY  
OPERATING  
**30-95**  
RANGE

ENERGY  
CONSUMPTION  
**1.4**  
kW

OPERATING  
RANGE  
**0-35**  
°C

## 3 SIZES FOR COMPLETE HUMIDITY EXTRACTION

Microwell industrial dehumidifiers are high-performance mobile appliances designed for high volume moisture extraction. With capacities of **40, 90** and **120** litres per day, they are well suited for any application. Often multiple units can be combined in a single application to provide massive yet very mobile drying. Additional electrical heater can be included with a dehumidifier to help speed up the drying process. As the applications are often harsh, all machines are extremely durable.

## FIT FOR HARSH TEMPERATURES

Equipped with a built-in electrical heating element, which ensures defrosting of the exchanger, Microwell industrial dehumidifiers are capable of operating at temperatures from 0°C to 35°C in any indoor area.

## APPLICATION OPTIONS

New construction sites, humid areas, drying up buildings, non-heated rooms, cellars, warehouses, switch rooms, filling stations, sports halls, garages, buildings flooded by water after fire-fighting to avoid corrosion, etc.

### T40 / TE40



up to 40 l/day

### T90 / TE90



up to 90 l/day

### T120 / TE120



up to 120 l/day

