




GREEN|R32|LINE



# HEAT PUMP

for swimming pool water  
heating & cooling

## Installation and user manual




Version: 05/2020



HP 1000 GREEN

&

HP 1400 GREEN





**Thank you** for purchasing Microwell swimming pool heat pump. Before you use this device, it is necessary to carefully read the entire Installation and user manual. It is not allowed to commence the heat pump installation or operation unless full content of this Installation and user manual is understood and acknowledged. Please keep the Installation and user manual available in the case of any future reference is required. Please provide this information also to each user of the device. Please mind local regulations in your country regarding installation and usage of this heat pump which are valid in addition to this User manual.

## Contents

1. INTRODUCTION .....	4
1.1 Product description .....	4
1.2 Package checking.....	5
1.3 Waste disposal information .....	5
2. SAFETY MEASURES .....	5
2.1 Electrical safety.....	6
2.2 Usage precautions .....	6
1) Warning .....	7
2) Attention .....	8
3) Safety.....	8
2.3 Handling precautions .....	9
2.4 Transportation.....	9
3. TECHNICAL SPECIFICATION .....	10
3.1 Technical data.....	10
3.2 Swimming pool water parameters .....	11
3.3 Heat pump dimensions .....	11
3.5 Installation reminder .....	12
3.6 Electric wiring Diagram.....	14
Reference for protecting devices and cable specification .....	14
4. REGULATION.....	15
4.1 Description of the LCD panel .....	15
4.2 Operation Instruction .....	15
5. TROUBLE SHOOTING FOR COMMON FAULTS .....	18
5.1 Repairing Guidance .....	18
5.2 Failure solution and code .....	18

6.	MAINTANANCE & WARRANTY .....	20
6.1	Maintanance.....	20
6.2	Warranty.....	21

## 1. INTRODUCTION

In your hands you hold probably the most advanced and the most efficient heat pump currently available on the market. This heat pump provides warm water in your pool at lowest possible cost. The heat pump is manufactured in tightest accordance with related strict standards and norms, in order to provide high quality operation and long-term reliability.

This Installation and user manual contains all the necessary information about the installation, operation and maintenance of the heat pump. Please read this Installation and user manual carefully before you start to use this product. The manufacturer is not responsible for any personal or property damage due to the improper installation, use or maintenance that is not in accordance with this User Manual.

This Installation and user manual is an inseparable part of this product; therefore it must be kept in good condition and must accompany the heat pump.

### 1.1 Product description

The heat pump is designed exclusively for swimming pool water heating or cooling and maintaining its temperature on the requested level. Other appropriate application is water temperature conditioning for fish tanks, wine ciders or horse cooling facilities. These applications should be discussed with local installer or distributor. Any other form of application is considered inappropriate.

The heat pump achieves the highest efficiency at 15÷35°C air temperature. At ambient air temperatures lower than -5°C the efficiency of the device decreases and at the temperatures higher than +40°C the heat pump can get overheated which may result in its malfunction, damage or failure. Do not use the product out of the designated operational air temperature range which is stated in section 3.1 *Technical data*.

This heat pump is designed for swimming pools with up to 40 m<sup>3</sup> - HP 1000 and up to 60 m<sup>3</sup> - HP 1400 of pool water volume. For proper operations there must be water flow through the exchanger of the heat pump (within water filtration circuit) in the range of 4-6 m<sup>3</sup>/h.

The heat pump enables heat gain from the external air surrounding the swimming pool through the compression – expansion cycles of the heat-carrying liquid. The air is driven by a fan through the evaporator where it will deliver its heat to the heat-carrying liquid (the air is being cooled at the same time). The heat-carrying liquid is then delivered to the spirals of the exchanger by the compressor which pressurises it and thus heats it up. In these spirals, the heat-carrying liquid delivers its heat to the swimming pool water. From the exchanger there is a cooled liquid flowing to the expansion valve or capillary where its pressure decreases and it gets cooled down rapidly at the same time. This cooled liquid flows to the evaporator again where it gets heated by the flowing air. The whole process runs fully automatically and is monitored by the pressure and temperature sensors. The same principle is applied when heat pump operates in cooling mode.

Using simple language, a heat pump is able to extract the heat/cold that is present in ambient environment and leveraged pass it into the pool water. When heating, higher the ambient air temperature is, more free energy can the heat pump extract and thus reach higher efficiency. At favourable conditions you pay around 15% of heat, i.e. 85% of heat is free. Please review below drawing of different ambient air conditions with subsequent efficiencies.

The heat pump efficiency grows by the increasing surrounding air temperature.

It takes some days to achieve the requested swimming pool water temperature. This time period depends on heat loss and heat gain balance of your pool.


**Example factors of heat losses:** poor pool construction, used materials, usage of cover, air – water temperature relationship, fresh water refilling, filtration, etc.

**Example factors of heat gains:** intensity of sun, winds, orientation of pool, air – water temperature relationship, etc.

In order to avoid heat loss when the swimming pool is not being used, it is highly advised to use pool's cover.

Ideal water temperature for external pools is considered at levels from 27° to 32°C. This may change based on particular demands of the user. When setting the desired air temperature higher than 32°C please review the material characteristics of your pool parts. High water temperature can damage these materials and contribute

to creation of algae. Manufacturer, distributor and reseller do not bear responsibility resulting from inappropriate heat pump usage.



## 1.2 Package checking

The unit was delivered in carton box on a wooden palette. Do not accept the package if it shows signs of damage. If the package appears intact, please unpack the unit and check the content. It should include the following:

1. The heat pump – condensing unit, the heat exchanger – indoor unit. Please see section 3.4 Description of the basic parts to see how the heat pump looks like
2. This Installation and user manual
3. Four rubber silent blocks

## 1.3 Waste disposal information

When using this heat pump in the European countries, the following information must be followed:

**DISPOSAL:** Do not dispose this product as unsorted municipal waste. It is prohibited to dispose this heat pump in domestic / household waste. It is prohibited to dispose this appliance into forests or natural landscape. This could lead into local soil pollution. Collection of such waste must be treated individually.



### DISPOSAL POSSIBILITIES:

1. The municipality has established a collection system where electronic waste can be disposed.
2. When buying a new product, the retailer or the manufacturer may take back the old appliance free of charge.
3. Old appliance may contain valuable resources which could be sold to scrap material dealers.
4. Disposal of packaging materials such as carton box or plastic / bubble foil can be recycled.



## 2. SAFETY MEASURES

It is necessary to follow instructions in this Installation and user manual and local regulations in your country that regulate the installation and usage of this device. Incorrect, improper or



operations contradictory to this Installation and user manual may lead to an injury or property damage and will lead to loss of warranty. To prevent injury or property damage the following instructions must be followed:

## 2.1 Electrical safety



- The device operates at dangerous electrical current.
- Only authorized person with particular electro-technical qualification can manipulate with unit.
- Danger of electrical shock.
- Do not exceed the required power supply.
- Do not turn the device on that shows signs of possible damage such as broken packaging, broken or otherwise damaged unit's chassis or cover, smoke, smell, etc.
- It is necessary to use appropriate Residual current circuit breaker (RCD) for connection of the heat pump to main power supply.
- Do not manipulate with the device with wet hands.
- Do not clean the device with water.
- Before cleaning the device, switch off the circuit breaker of the unit's power supply.
- Installation, service or repair must be performed by qualified technician.
- When the device is not intended to be used for a longer time, we recommend switching the circuit breaker of the unit's power supply off.
- Unit must be installed in vertical position to avoid condensate water to enter electrical part of the unit.
- It is forbidden to install the unit close to devices that may cause electrical or frequency disturbance such as welding machines, motors or rotors, WIFI/WLAN routers or repeaters.
- It is forbidden to alter electrical installation of the device. It is also forbidden to alter any other part or functionality of the device.

## 2.2 Usage precautions



Do not cover or block the intake or exhaust opening / ventilator and evaporator covers. It is forbidden to block or cover the intake or exhaust openings with clothes, towels, buckets, canoes, trees, etc. Such action would lead to a decrease of needed airflow. That would result in heat pump inefficiency and underperformance, eventually to heat pump overeat with subsequent security turning off, malfunction, failure or damage. Especially during bloom months it is highly advised to keep the evaporator fins clean.

- Do not climb up on or sit on the unit.
- Do not place any objects on the top of the unit (e.g. boxes, flower vases, etc.).
- Do not spray any flammable substances into the equipment; this might lead to fire.
- Do not clean the equipment with aggressive cleaning agents, this might lead to damage or deformations.
- When cleaning plastic parts do not use any cleaning agents unsuitable for plastic (household cleaning agents, solvents, bleaching agents, benzene, diluents, rough cleaning powder, cresol, chemical agents). Instead, sweep the heat pump cover with a soft cloth or a sponge.
- Never throw or insert any objects into any hose or opening.
- The cover is made of metal. Do not manipulate with lighted cigarette, cigarette ashes, or any other kind of fire in vicinity to this part.
- Use this device exclusively for the intended purpose, as described in the attached instruction manual. Do not use parts which are not recommended.
- Never block the air opening of the product. Protect the air openings from clogging by particles.
- Do not drink or use the condensate water drained from the unit. Do not return the water back to the swimming pool. The water may be contaminated with bacteria.
- Children are not allowed to operate, touch or play with the unit.
- **Children are not allowed to manipulate with packaging, plastic / bubble foil. Risk of suffocation!**
- Prevent the children from injury or harm caused by any manipulation with the unit, its parts or its

packaging. Small parts like screws may be swallowed and cause harm to health.



- Do not leave the children in the swimming pool / at the swimming pool unattended.
- The positioning of the heat pump must be in accordance with the STN 33 2000-7-702 standard, i.e. it must be placed at least 3,5 m from the swimming pool's external border.
- For heating/cooling the swimming pool by the heat pump, the filtration pump must run and the water must flow through the heat exchanger.
- Never turn on the heat pump if it is without water and if the filtration device is not operating.
- Protect the heat pump from freezing. Eliminate the water from the filtration and from the heat pump's water heat exchanger and prepare the product for the winter time.
- At low surrounding ambient temperature level (below 10°C) and high relative air humidity level (e.g. after rain, during the night, etc.), the evaporator may get iced up. Heat pump will automatically defreeze itself. Its operations or functionality is not harmed but the efficiency decreases.
- Manufacturer does not bear any responsibility concerning damages caused by inappropriate heat pump selection, installation or application.
- Do not pressurize the water heat exchanger higher than 0.25MPa (2.5bar). By pressure of 0.5MPa (5bar) the water heat exchanger gets irreversibly damaged. It is advised to install a security valve with pressure threshold at 0.25MPa (2.5Bar) before the heat exchanger.
- Do not apply or use water of higher temperature than 45°C in water heat exchanger. Water temperature above 60°C irreversibly damages the water heat exchanger.
- Manufacturer does not bear any responsibility concerning damages caused by inappropriate heat pump performance and/or model selection, installation or application. Heat pump is considered undersized in the case it works usually and in long-term more than 18 hours daily. General warranty void applies for damages on the device or other damages if the device works usually in long-term more than 18 hours daily.
- The heat pump must be correctly sized for its application.
- Refrigerant connection between the water and the condensing unit must comply with local refrigerant regulations. Typically, the refrigerant circuit must be sealed. Manufacturer does not bear any responsibility for damages caused by incorrect refrigerant works.

## 1) Warning



a. The WARNING sign denotes a hazard. It calls attention to a procedure, practice, or the like, which, if not correctly performed or adhered to, could result in personal injury or injury to a third party. These signs are rare, but are extremely important.

	a. Keep the heat pump away from fire source.
	b. It must be placed in well ventilated area, indoor or closed area is not allowed.

	c. Repair and disposal must be carried out by trained service personnel
	d. Vacuumize completely before welding. Welding can only be carried out by professional personnel in service center.

## 2) Attention

- Please read the following instructions before installation, use and maintenance.
- Installation must be done by professional staff only in accordance with this manual.
- A leakage test must be performed after installation.
- If a repair is required, please contact the nearest after-sales service center. The repair process must be strictly in accordance with manual. All repair practice by non-professional is prohibited.
- Set proper temperature in order to get comfortable water temperature to avoid overheating or overcooling.
- Please don't stack substances, which will block air flow near inlet or outlet area, otherwise the efficiency of the heater will be reduced or even stopped.
- Don't use or stock combustible gas or liquid such as thinners, paint and fuel to avoid fire.
- In order to optimize the heating effect, please install heat preservation insulation on pipes between swimming pool and the heater, and please use a recommended cover on the swimming pool.
- Connecting pipes of the swimming pool and the heater should be  $\leq 10\text{m}$ .

## 3.) Safety

- Please keep the main power supply switch far away from the children.
- When a power cut happens during operating, and later the power is restored, the heater will start up.
- Please switch off the main power supply in lightening and storm weather to prevent from machine damage that caused by lightning;
- Any repairing should be conducted in the area with good ventilation. The ignition source is prohibited during the inspection.
- Safety inspection must be carried before the maintenance or repair for heat pumps with R32 gas in order to minimize the risk.
- If R32 gas leaks during the installation process, all operations must be stopped immediately and call the service center.




### 2.3 Handling precautions




- *Transport in lying position or turning the device over may harm the compressor resulting in unit's malfunction, failure or damage and will lead to loss of warranty.*
- *The device must be handled with care and special attention avoiding any mechanical damage.*
- *It is forbidden to apply any improper mechanical force onto the unit. This may cause mechanical damage to the device.*
- *It is forbidden to let the device fall freely onto the ground or any solid surface resulting in hard impact.*
- *Please notify your reseller or distributor if you suspect that the unit was delivered damaged. Unit may seem to work well at start but small damage can make the unit go out-of-order in short time. In such case the unit must be inspected and approved for further use by your reseller.*
- *Please notify your reseller or distributor if directly after installation you suspect that unit is not working in perfect order.*
- *In the case of device failure resulting from improper handling or mechanical damage (impact, hit, fall, etc.), the manufacturer reserves the right to evaluate the continuity of warranty.*

### 2.4 Transportation

a. Always keep upright



b. Do not lift the water union  
( If so, the titanium heat exchanger  
inside the heat pump may be damaged)



### 3. TECHNICAL SPECIFICATION

#### 3.1 Technical data

Model	HP1000 GREEN	HP1400 GREEN
<b>PERFORMANCE CONDITION: Air 27°C/ Water 27°C/ Humid. 80%</b>		
Heating capacity (kW)	9.8	14.2
C.O.P.	5.8	5.7
<b>PERFORMANCE CONDITION: Air 15°C/ Water 26°C/ Humid. 70%</b>		
Heating capacity (kW)	7.0	10.0
C.O.P.	4.3	4.3
<b>PERFORMANCE CONDITION: Air 35°C/ Water 28°C/ Humid. 80%</b>		
Cooling capacity (kW)	4.1	6.0
<b>TECHNICAL SPECIFICATIONS</b>		
Advised pool volume (m <sup>3</sup> )	30~45	40~65
Operating Air Temperature(°C)	0°C~43°C	
Rated input power ( kW )	1.5	2.3
Rated input current (A)	6.8	10.6
Max input current (A)	<u>11.5</u>	<u>15.5</u>
Breaker (A)	<u>14.0</u>	<u>19.0</u>
Power Cord (mm <sup>2</sup> )	<u>3×2.5</u>	<u>3×4.0</u>
Power supply	230V/1 Ph/50Hz	
Heat exchanger	Titanium in PVC	
Casing	ABS Casing	
Advised water flow (m <sup>3</sup> /h)	4~6	5~7
Sound pressure 1m dB(A)	48.6	52.1
Sound pressure 10m dB(A)	28.6	32.1
Water connection (mm)	50	

\* The manufacturer reserves the right to change the parameters without notice.

\*\* In the case Winter module, condensate tray antifreeze or heat exchanger frost protection is installed.

The refrigerant circuit is filled with R32.

Refrigerant R32 also called HFC-32 or difluoromethane. R32 is a molecule used as refrigerant that has zero ozone depletion potential (ODP).

R32 with the global warming potential (GWP) index 675 times that of carbon dioxide, based on a 100-year time frame, and it is classified as A2L - slightly flammable by ASHRAE.

### 3.2 Swimming pool water parameters

The heat pump is designed for heating the swimming pool water. Although the water heat exchanger is made from the most durable titanium, in order to ensure long term reliability of the heat pump the pool water must be in accordance with the related sanitary requirements.


The limit values for the heat pump operation are the following:

- pH value ranging from 6.8 to 7.9,
- total chlorine amount not exceeding 3 mg/l,
- salt content 6% wt/wt.

Should you have different values of pH, chlorine or salt please try to apply appropriate agents or contact your swimming pool builder to resolve the situation. Above mentioned values are recommended for pools in general.

It is also advised to keep the water hardness on the lower limit of the optimal range, i.e. closely above 8 °N.

### 3.3 Heat pump dimensions




	A	B	C	D	E	F	G	H
<b>HP1000 GREEN</b>	315	590	318	340	986	280	74	657
<b>HP1400 GREEN</b>	395	590	398	420	987	310	74	657

*Note: The illustrations and descriptions found in this Installation and user manual are not binding. The manufacturer reserves the right to make corrections or changes without notice.*

### 3.4 Description of the basic parts

#### CONDENSING UNIT



- Legend:**
- 1 – Protecting grates of the fan (air outlet) / ventilator cover
  - 2 – Cover / ABS chassis
  - 3 – Control panel
  - 4 – Valve for refilling the refrigerant (under the cover)
  - 5 – Power supply connection (underneath the plastic cover)
  - 6 – Evaporator (air inlet)
  - 7 – Water outlet connection hub
  - 8 – Water inlet connection hub


### 3.5 Installation reminder


Only a professional staff is allowed to install the heat pump. The users are not qualified to install by themselves, otherwise the heat pump might be damaged and risky for users' safety.

#### a. Location and dimension




The pool heat pump should be installed in a good ventilation place.





- 1) The frame must be fixed by bolts (M10) to concrete foundation or brackets. The concrete foundation must be solid and fastened; the bracket must be strong enough and antirust treated;
- 2) Please don't stack substances that will block air flow near inlet or outlet area, and there is no barrier within 50cm behind and 250cm in front of the machine, or the efficiency of the heater will be reduced or even stopped;
- 3) The machine needs an appended pump (Supplied by the user). The recommended pump specification-flux: refer to Technical Parameter, Max. lift  $\geq 10\text{m}$ ;
- 4) When the machine is running, there will be condensation water discharged from the bottom, please pay attention to it. Please hold the drainage nozzle (accessory) into the hole and clip it well, and then connect a pipe to drain the condensation water out.


**b. The inlet and outlet water unions can't stand the weight of soft pipes. The heat pump must be connected with hard pipes!**



### 3.6 Electric wiring Diagram

- Connect to appropriate power supply, the voltage should comply with the rated voltage of the products.
- Earth the machine well.
- Wiring must be handled by a professional technician according to the circuit diagram.
- Set leakage protector according to the local code for wiring (leakage operating current  $\leq 30\text{mA}$ ).
- The layout of power cable and signal cable should be orderly and not affecting each other.

#### Electric wiring Diagram - For power supply: 230V 50Hz



#### Reference for protecting devices and cable specification

MODEL		HP1000 GREEN	HP1400 GREEN
Breaker	Rated Current (A)	14.0	19.0
	Rated Residual Action Current mA	30	30
Fuse (A)		14.0	19.0
Power Cord (mm <sup>2</sup> )		3×2.5	3×4.0
Signal cable (mm <sup>2</sup> )		3×0.5	3×0.5


※ Above data is subject to modification without notice.

**Note:** The above data is adapted to power cord  $\leq 10\text{m}$ . If power cord is  $> 10\text{m}$ , wire diameter must be increased. The signal cable can be extended to 50m maximumly.



4. REGULATION

4.1 Description of the LCD panel










Symbol	Designation	Function
	ON/OFF	Power On/Off
M	Mode	Heating , cooling , auto
SET	Setting	Check system temperature and set the time
	UP/DOWN	Temperature Setting & Displaying
	Time	Set the timer


4.2 Operation Instruction

1). Time setting

Long press the **SET** key 5s to set the time according to your local time. When the time on the screen is flashing, press the key **▲,▼** to adjust the hour. Press the **SET** key to confirm the hour, and it begins to adjust the minutes. Press the key **▲,▼** to adjust the minutes. It will return to the main interface by pressing the **SET** bottom or no operation for 10 seconds.

## 2). Timer Switch on and Switch off

Press the  key 5s to enter the timer Switch ON setting. When the time on the screen is flashing, press the ,  to adjust the hour. Press the  to confirm the hour and enter the minutes setting. Press the ,  to adjust the minutes. Press again the  to confirm the Timer Switch ON and enter Timer Switch Off setting. The operation is the same as the Timer Switch ON. If there is no operation during 10 seconds, it will confirm the current Timer setting, and return to the main interface. When the Timer ON/OFF is activate, you can see **ON/OFF** at the right bottom of the main interface.

Press the  key 5s to enter the timer Switch ON setting, and press the **SET** bottom to cancel the timer setting.


## 3). Information checking.

### A: Check the current temperature

Press the **SET** key at the main interface to check the system temperature. Press the **SET** key again to check each temperature value. It will return to the main interface when there is no operation during 10 seconds.

Statue	NAME	Range	N.B
13	Water-in temps	-9°C~99°C	Measured value
14	Water-out temps	-9°C~99°C	Measured value
15	Evaporator Coil pipe temps	-9°C~99°C	Measured value
16	Gas return temps	-9°C~99°C	Measured value
17	Ambient temps	-9°C~99°C	Measured value
18	Cooling coil pipe temps	-9°C~99°C	Measured value
19	EEV steps	150P~ 470P	Measured value

B: Check system parameters.

Press “M” and “  ” for 5s to check parameters and press the ▲, ▼ to check different parameter data 0~12.

*Notice: Manufacturer reserves the right to change parameters or controller functions without notice.*

**System parameter:**

Data	Meaning	Range	Default
00	Cooling water return temp	10℃～30℃	12℃
01	Heating water return temp	18℃～40℃	40℃
02	Auto mode water return temp	10℃-40℃	30℃
03	Defrosting cycle under heating mode	30Min～90Min	40Min
04	Defrosting start temp	-30℃～0℃	-7℃
05	Defrosting exit temp	2℃～30℃	13℃
06	Defrosting exit time	1Min～12Min	12Min
10	Water pump mode	0(Standard)/1(Special)	1
11	Overheating of electronic expansion valve in heating mode	-F(-15℃)～F(15℃)	3℃
12	Overheating of electronic expansion valve in cooling mode	-F(-15℃)～F(15℃)	5℃

4). Keyboard lock & unlock

Long press the keys ▲ and ▼ at the same time 5s at the main interface to lock and unlock the keyboard.

## 5. TROUBLE SHOOTING FOR COMMON FAULTS

### 5.1 Repairing Guidance



#### WARNING:

- a. If repair or scrap is required, pls contact authorized service center nearby.
- b. Requirements for Service Personnel
- c. Any person who is involved with working on or breaking into a refrigerant circuit should hold a current valid certificate from an industry-accredited assessment authority, which authorizes their competence to handle refrigerants safely in accordance with an industry recognized assessment specification.
- d. Do not attempt to work on the equipment by yourself. Improper operation may cause danger.
- e. Strictly comply with the manufacturer's requirements when charging R32 gas and equipment maintenance. This chapter focuses on special maintenance requirements for swimming pool heat pump with R32 gas. Please refer to the technical service manual for detailed maintenance operation.
- f. Vacuumize completely before welding. Welding can only be carried out by professional personnel in service center.

### 5.2 Failure solution and code

Failure	Reason	Solution
Heat pump doesn't run	No power	Wait until the power recovers
	Power switch is off	Switch on the power
	Fuse burned	Check and change the fuse
	The breaker is off	Check and turn on the breaker
Fan running but with insufficient heating	evaporator blocked	Remove the obstacles
	Air outlet blocked	Remove the obstacles
	3 minutes start delay	Wait patiently
Display normal, but no heating	Set temp. too low	Set proper heating temp.
	3 minutes start delay	Wait patiently
If above solutions don't work, please contact your installer with detailed information and your model number. Don't try to repair it yourself.		

**Note:** If the following conditions happen, please stop the machine immediately, and cut off the power supply immediately, then contact your dealer:

1. Inaccurate switch action.
2. The fuse is frequently broken or leakage circuit breaker jumped.

### Protection & Failure code

Failure code	Protection & Failure
PP 01	Water inlet temp sensor failure
PP 02	Cooling coil pipe temp sensor failure
PP 03	Evaporator coil pipe temp sensor failure
PP 04	Gas return temp sensor failure
PP 05	Ambient temp sensor failure
PP06	High exhaust temp protection
PP 07	Ambient temperature too low protection
PP 08	Water outlet temp sensor failure
EE 01	High pressure protection
EE 02	Low pressure protection
EE 03	Low water protection
EE 04	Failure connection due to loose wire terminal of PROT2 on the PC board
HEATING icon flashing	Defrosting (not failure)
EE 08	Communication failure


## 6. MAINTANANCE & WARRANTY

### 6.1 Maintenance



**“CUT OFF” power supply of the heater  
before cleaning, examination and repairing**

1. In winter season when you don't swim:
  - a. Cut off power supply to prevent any machine damage.
  - b. Drain water clear of the machine.



**!!!Important:**

Unscrew the water nozzle of inlet pipe to let the water flow out.

*When the water in machine freezes in winter season, the titanium heat exchanger may be damaged.*

- c. Cover the machine body when not in use.
2. Please clean this machine with household detergents or clean water, NEVER use gasoline, thinners or any similar fuel.
3. Check bolts, cables and connections regularly.
4. If repair or scrap is required, pls contact authorized service center nearby.
5. Do not attempt to work on the equipment by yourself. Improper operation may cause danger.
6. In case of risking, safety inspection must be carried before the maintenance or repairing for heat pumps with R32 gas.



## 6.2 Warranty

Your heat pump is covered by warranty. For particular conditions of this warranty in terms of warranty period and subject please refer to your local regulations and/or agreement with your distributor, reseller or installer. Any action resulting in damage of the heat pump, property or other damage caused by improper usage of this product or in contrary with this Installation and user manual is excluded from warranty coverage.

**Notes:**

Notes:

Distributed by:

**Manufacturer:**



MICROWELL, spol. s r.o.  
SNP 2018/42, 927 01 Sala, Slovakia



tel.: +421/31/702 0540



fax: +421/31/702 0542

e-mail: microwell@microwell.sk

www.microwell.eu

